



Tax-Xwieki,
Limits of Naxxar GHR 9013 - Malta.
Tel: (00356) 21 418 411 / 2 / 3
Mob: (00356) 79 418 411
Fax: (00356) 21 435 395
E-mail: info@bitmac ltd.com
VAT No: MT1301 1627

Blackflex

Rubberised Bituminous Emulsion

BX 0777

General Description: Rubber (Latex) improved, Bitumen liquid membrane.

Main Characteristics: Excellent weather resistance;
Very easy to apply by spreading or brushing;
Remains flexible;
May be applied to horizontal or vertical surfaces
Excellent for waterproofing wells, cellars etc.;;
May be reinforced with **Geotextile**
Use **water** for thinning and cleaning tools;

Colours: Only available in matt black.

Technical data at 20°C

Mass density:	Approximately 1.45gm/cm ³
Solids content by volume:	Approx. 48%
Suggested dry film thickness:	90-200 um per coat
Practical spreading rate:	1 sq.mtrs per litre
Dust dry after:	2 hours, depending on local humidity/temperature
Min. interval before over coating:	12 hours
Shelf life (in airtight containers):	Up to 2 years.
Flashpoint:	Not applicable, water –based.

Instructions for use:

Mixing Instructions: Stir thoroughly before use, ensuring no solids at base of container

Thinning of Blackflex: Clean water may be used to thin the paint, to improve the brushing, but small quantities should be added slowly with stirring, to ensure that over-thinning does not occur.

Application: Blackflex may be applied by brush, roller or spray.
Please contact BX Coatings for Technical advice on spraying.

Cleaning: Wash all tools with water immediately after use, preferably with hot or warm water.

Safety precautions: As with all chemicals, contact with skin or eyes must be avoided. Accidental contact with skin may be removed with water and a small brush. Avoid prolonged breathing in confined areas.

