

SABBIAFOND



Primer based on water

Good penetration

It is suitable for inner rooms



Code

0624

Description

It is a stabilizing fixative product, that can be diluted in water, based on styrene – acrylic copolymers.
Since it is pigmented, it gives an initial covering of the support.

Use

This product is suitable to consolidate and make uniform new and old plasters, concrete surfaces, old paints, but they must be dry and well adherent. In addition to improve all the features of the plaster, it gives a better application of all the decorative products, favouring the perfect adherence.

Appearance of the film

Matt

Colour

White – color chart

Component

1

Hardening

Evaporation of the solvents and union of the polymer

Specific weight	1,570 gr/ml
Volume of solids	45,5%
VOC	15 gr/ liter
Minimum thickness	50 micron
Estimated yield	9,1 m ² / litre for a thickness of 50 micron
Flash point	Component A >113°
Preparation of surfaces	Make sure that the support is completely dry, remove possible efflorescence and old paints that are peeling off with brushes. Remove totally old layers of lime and tempera paint.
Preparation of the product	Mix the product before the use
Thinning	20 – 25% with water
Environmental conditions	Ambient temperature: from + 5° C to 35° C Temperature of the support: > 5° C Humidity: 0 % – 75 % Avoid the applications if there is a surface condensation or under the direct action of the sun.
Drying and hardening time	25° C and 65 % relative humidity 35 – 45 minutes
Time of overpainting	4 – 5 hours

Application

Brush, roller

If you use the brush, you have to use nylon or natural bristle brushes.

If you use the roller, you have to use medium-haired rollers.

For the application, it is necessary to use the method of crossing coats.

Shelf life

1 year in a cool and dry place (max 40° C)

Packs

Lt. 14 Lt. 5 Lt. 2,5

