DGHT0D6/5035/KH

Highway D400 3 flange gully grate 480mm x 320mm clear opening with 150mm frame depth



RANGE	CLEAR OPENING (MM)	BASE OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)	WATERWAY AREA (CM^2)	OPTIONS
Highway	480 x 320	500 x 350	675 x 445	150	950	☐ Screw locking

FEATURES

- Non rocking 3-point suspension design, for silent operation.
- Captive hinges reduce theft risk whilst allowing easy lifting.
- Frame gussets are supports which reinforce the corners where the frame sections meet, distributing stress evenly, preventing damage to the frame or the access cover.
- Holes in the frame flange where mortar can pass between the underside and top side, creating an interlock, providing greater strength.
- Surface texturing above and below the flange enables better mortar engagement, reducing any lateral movement which could result in cracking.
- Meets the requirements of CD 534 v0.1.0 (formerly HA 104/09).
- The enlarged frame corners help to dissipate loads onto the foundation, providing a longer service life and increased reliability.
- Keyway lifting points are provided on the frame for safe handling.
- Reversible hinge allows the grating to hinge with the direction of the traffic flow, improving safety.

Tel: 01543 440 440
wrekinproducts.com



SPECIFICATION

General information

Stock code	DGHT0D6/5035/KH
Primary material	Ductile iron
Range	Highway
Category	Gully grate
Flanges	3

Standards, classes and groupings

Standards	BS EN 124-2 DMRB MCHW CD 534 v0.1.0

Tel: 01543 440 440
wrekinproducts.com

BS EN 124 Class	D400
BS EN 124 Group	3 4
Third party certified	Kitemark
CD 526 hydraulic capacity	R

Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	675 mm x 445 mm
Clear opening (C x D)	480 mm x 320 mm
Frame depth (E)	150mm
Base opening (F x G)	500 mm x 350 mm
Waterway area	950cm²

AVAILABLE OPTIONS

Screw locking
Screw locking deters unauthorised access to the chamber. An extended shank socket set is required to engage the locking screw.

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak® rapid curing polyester resin mortar

STOCK CODE	DESCRIPTION
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar
SCREWLIFT	Simple and rapid manhole frame levelling system. Simply push the bushes into the holes in the flange and adjust the levelling screws to the required height.

NOTES

Compatible with

Stock code	Description
DGCC/6545/G	H2GO gully chute connector 655mm x 450mm x 185mm with 150mm and 160mm spigot sizes

Where 3-flange D400 Gully Grate assemblies are employed, we recommend that they are installed against a kerb, not in an open highway location.

The D400 load capability of these Group 3 products also offers the benefit of making them suitable for exposure to Group 4 traffic types. Where 3-flange D400 Gully Grate assemblies are employed, we recommend that they are installed against a kerb, not in an open highway location. All values stated are nominal within 2.5% tolerance.

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our Terms and Conditions of Sale